Waterproof Battery Chargers

AQUANAUTIC Waterproof range

The Waterproof **Aquanautic** battery charger is a fully sealed, fully waterproof and fully dust ingress/proof built to IP67 marine grade battery charger. The charger features **active power factor correction**, this allows for global **AC input (90VAC-270VAC)** and improved efficiency.

- Power Factor Corrected(active) 0.99-1 (PFC)
- 90VAC-270VAC input (47-70Hz).
- Extruded aluminum housing.
- Pre-fused and pre-wired with 1.5 m cable.
- waterproof built to IP67 standard.
- Adaptive charging, ensuring maximum charge in the batteries.
- LED power and charge indicators.
- Pre-fused and gold plated terminals.
- Up to 3 isolated outputs.
- Preset charging profiles AGM, Gel, flooded lead acid.
- Available in 8A / 12A / 20A
- Available in 12V / 24V / 36V
- Dynamic thermal output control, reduces power rather than over heats.

Alexandra Produces

Waterproof Aquanautic PFC 1			10-230V Active Power Factor Correction				
Output (V)	Out	out(s) Curre	ent(A) Si	ze L x W	x D mm	Weight Kg	SKU
12	1	8		180 x 17	0 x 65	2.5	PSP1281
12 & 24	2	8 at 12V 4 a	at 24V	180 x 170) x 65	2.5	PSP1282
12	1	12		200 x 17	0 x 65	2.8	PSP12121
12 & 24	2	12 at 12V 6	at 24V	200 x 170) x 65	2.8	PSP12122
12	1	20A/12	2V	290 x 17	0 x 65	3.8	PSP12201
12 & 24	2	20A/12V 10	A/24V	290 x 17	0 x 65	3.0	PSP12202
12 & 24 & 30	63	20A/12V 10A	/24V 6A/36V	290 x 17	0 x 65	3.2	PSP12203

The Pro Sport 5 and 5/5

A range of battery chargers designed to IP68 standard. Available in 5A and 10A models. 12V and 24V.

- 12V 5A and 24V 5A (10A at 12V 2 output)
- Moulded plastic case.
- Ignition Protected
- Epoxy filled, IP68 proofing.

 Adaptive charging, ensuring maximum charge in the batteries.

- LED power and charge indicators.
- Pre-fused and pre-wired with 1.5 m cable.
- Up to 3 fully isolated outputs.

– Dynamic thermal output control, reduces power rather than over heats.



The Pro Sport 5 12V 5A only The Pro Sport 5/5 12V and 24V

Pro Sport 5 and 5/5 Waterproof Battery Charger 230V AC 50 Hz only					
Current	(V) Current (A)	Output(s)	Size L x W x D mm	Weight kg	SKU
12	5	1	75 x 150 x 65	2.5	PS125
12/24	12V (2 x 5A) / 12V (1 x	(10A) 2	230 x 130 x 90	3.5	PS1255
	or 24V (1 X 5A)				

This 1A float charger is ignition protected and IP68 waterproof. The charger is pre-wired and only works at 12V. It is ideal for jet bikes, small boats, lawn mowers etc.

		1A Float Charger		
(V)	(A)	Size L x W x D mm	Weight Kg	SKU
12	1	60 x 60 x 60	0.5	121CE

